

Chevron Delo® Bumper-to-Bumper Protection for Construction Equipment

Hydraulic System

- Delo TorqForce® MP (CAT TO-4M)
- Delo TorqForce 10W (CAT TO-4)
- Delo TorqForce Syn 5W-20
- Rando® HDZ
- Ursa Hydraulic Oil 10W

Transmissions

- Delo TorqForce MP (CAT TO-4M)
- Delo TorqForce 30 (CAT TO-4)
- Delo 400 10W (hydrostatic)
- Delo Syn-Trans HD 50

Engine Crankcase

- Delo 600 ADF 15W-40
- Delo 400 XSP 5W-40
- Delo 400 XLE 10W-30
- Delo 400 XLE SB 15W-40

Bearings and Grease Points

- Rykon® HD
- Rykon HD M5
- Starplex® HD
- Starplex HD M5
- Starplex Syn EP M5
- Starplex HD M3

Coolant System

- Delo ELC Advanced Antifreeze/Coolant
- Delo ELC Antifreeze/Coolant
- Delo XLC Antifreeze/Coolant

Differentials and Gear Drives

- Delo Syn-Gear XDM 75W-90
- Delo Gear ESI 80W-90
- Delo TorqForce 50 (CAT TO-4)
- Delo Syn-Gear HD 75W-90

Available as ISOCLEAN® Certified

These product recommendations provide general guidelines. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. Visit chevron-gsc.force.com/lubeteksupport for confirmation of specific OEM specifications.



A Chevron company product

©2023 Chevron. All rights reserved. All trademarks are property of Chevron Intellectual Property LLC or their respective owners.