

Delo® Protection for Construction Equipment



Hydraulic System

- Delo TorqForce™ 10W (CAT TO-4)
- Delo TorqForce MP (CAT TO-4M)
- Delo TorqForce Syn 5W-30
- Rando® HDZ
- Ursa Hydraulic Oil 10W



Bearings and Grease Points

- Delo Grease ESI® HD EP
- Delo Grease ESI HD Moly 5% EP
- Delo Syn-Grease™ SXD 220 Moly 5% EP
- Delo Grease ESI HD Moly 3% EP



Transmissions

- Delo TorqForce 30 (CAT TO-4)
- Delo TorqForce MP (CAT TO-4M)
- Delo 400 10W (hydrostatic)
- Delo Syn-Trans HD 50



Engine Crankcase

- Delo 400 XSP 5W-40
- Delo 400 XLE 15W-40
- Delo 400 XLE 10W-30
- Delo 400 SDE 15W-40
- Delo 600 ADF 15W-40



Coolant System

- Delo XLC Antifreeze/Coolant
- Delo ELC Antifreeze/Coolant
- Delo ELC Advanced Antifreeze/Coolant

Differentials and Gear Drives

- Delo Syn-Gear XDM 75W-90
- Delo Gear ESI 80W-90
- Delo TorqForce 50 (CAT TO-4)
- Delo Syn-Gear HD 75W-90



Available as ISOCLEAN® Certified

The product recommendations provide general guidelines for use in construction equipment. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. Visit chevron-gsc.force.com/lubeteksupport for confirmation of specific OEM specifications.



Delo®

Let's go further.®

A Chevron company product

©2022 Chevron. All rights reserved. All trademarks are property of Chevron Intellectual Property LLC or their respective owners.

DLPTCNEQST_02-22